

US VACUUM “CP” Series Rotary Vane Vacuum Pumps



5-15 cfm Vacuum: 29.9” Hg

US Vacuum “CP” series vacuum pumps are Single Stage Rotary Vane Air-Cooled vacuum Pumps capable of producing an ultimate vacuum to 29.9” Hg.

All CP pumps features a compact, simple design; quiet air-cooled operation; direct drive 110V motor; power cord and on-off switch. The CPS-15D includes as standard an integral oil mist exhaust filter for oil free discharge. As with all CP pumps require no water for cooling; no belts or gears to wear or loosen; and light weight for portability.


All CP pumps are ideally suited for use in applications such as vacuum bagging, composite molding, vacuum hold-down, degassing and sampling.

FEATURES

- Ultimate vacuum of 29.9” Hg
- Low Cost
- Compact design
- Air-cooled



SAME DAY SHIPMENT
when ordered by 12:00 PM



CPS-5B/8B



CPS-7D/15D

MODEL		CPS-5B	CPS-8B
Displacement	CFM	5	8
Ultimate Vacuum	Torr	29.9" Hg	
Noise Level	dba	54	56
Motor	Hp	1/3	1/2
Pump Speed	RPM	1750	1750
Oil Capacity	ml	250	600
Inlet Connection	inches	3/8"	
Dimensions (inches)	L x W x H	13.25 x 5.5 x 10	15 x 5.75 x 11
Pump Weight	Lbs.	23	44
PRICE	USD	\$350	\$450

	CPS-7B	CPS-15B
Displacement	7.5	15
Ultimate Vacuum	29.8" Hg	
Noise Level	70	72
Motor	1	1.5
Pump Speed	1750	3500
Oil Capacity	500	500
Inlet Connection	1/2"	
Dimensions (inches)	19.5 X 10.5X 9.5	19.5 x 10.5 x 8.5
Pump Weight	42	42
PRICE	\$1,080	\$1,080

OPTIONAL EXHAUST FILTER	\$110
OPTIONAL INLET FILTER	\$75
OPTIONAL VACUUM GAUGE	\$35

Standard	Standard
\$75	
\$35	

RECOMMENDED USAGE **LABORATORY**

INDUSTRIAL

888-416-7366