

US VACUUM PUMPS LLC

USV-15F

ROTARY VANE SINGLE STAGE VACUUM PUMP



US VACUUM pump Model USV-15F is a Single stage, Air-cooled, Rotary vane vacuum pump capable of producing an ultimate vacuum to 2 mm Hg (29.8" Hg).

The pump is small and compact yet produces a very generous 15 cfm of inlet pumping capacity. Typical applications include vacuum drying, impregnation, food packaging, vacuum chucking and de-gassing.

Available standard with either 120v or 240v (1-ph) programmable Control panel w/ pressure transducer.


TECHNICAL DATA

PUMP TYPE	USV-15F	
Pump Displacement	CFM	15
Ultimate Vacuum	Torr	2
Pump Speed	RPM	3500
Oil Capacity	ml	500
Inlet connection	Inch	1/2
Motor-Installed power	HP	1.5
Weight	LBS	42
Noise level	db(A)	72

Vacuum Tank system

- 15 cfm Vacuum pump
- 15 gallon tank
- 1.5hp Motor
- Inlet Filter
- Pressure Transducer
- Programmable Control Panel w/ Digital display and H-O-A switch
- Rubber mounts
- 120V & 230V (1-PH)






BILL OF MATERIAL			
NO.	QTY	DESCRIPTION	PART NUMBER
1 1 VACUUM PUMP MODEL CPS-15D		VACUUM PUMP MODEL CPS-15D	CPS15D11060
2	1	ELECTRIC MOTOR 1-1/4HP, 110V, 60HZ	EMCPS15B1.25
3	1	ISOLATION VALVE, BRASS 1/2"	IBVCPS15B.50
4	1	CHECK VALVE, ALUMINUM 1/2"	CVCPS15B.50
5	1	VACUUM GAUGE, LIQUID FILLED, BRASS 1/4"	VGCPS15B.25
6 1 PARTICULATE FILTER		PARTICULATE FILTER	VFISL824050
7	1	TANK, 15 GALLON	US302464
8 1 CONTROL PANEL, PROGRAMMABLE, DIGITAL DISPLAY		CONTROL PANEL, PROGRAMMABLE, DIGITAL DISPLAY	MSCPS15B110

PLAN

- 20.00 -

END VIEW



NOTES:

CPS-15D

- 1. ALL STANDARD UNIT PIPING SHALL BE SCH/40 ASTM A-53 TYPE F C/W 150# ASTM A-197 MALLEABLE IRON THREADED FITTINGS.
- 2. DIMENSION TOLERANCE TO 1/4".
- 3. CUSTOMER IS RESPONSIBLE FOR PROPER LIFTING EQUIPMENT FOR LIFTING SKID.
- 4. ANCHOR BOLTS ARE NOT FURNISHED WITH UNIT.

ELEVATION

PROJECTION

INITIAL RELEASE PD PD 20-JUL-11 REV DESCRIPTION DWN CK APP DATE CERTIFIED DRAWING DWN **US VACUUM PUMPS, LLC** APP SCALE 3/4"=1'-0"

DIMENSIONS ARE IN INCHES [mm] WEIGHT IN LBS [kg] VACUUM PUMP SYSTEM w/ HORIZONTAL RECEIVER P.O. BOX 909 CANTON, TEXAS 75103 PH: 888-416-7466 / FAX: 877-416-7599

DWG. NO. REV CPS15D-01 0